MISSISSIPPI'S BMP IMPLEMENTATION MONITORING PROGRAM

2003 BMP Implementation Survey

Survey Period

November 2002—July 2003

PREPARED BY
MICHAEL SAMPSON,
FOREST MANAGEMENT
DIVISION



301 North Lamar St., S-300 Jackson, Mississippi 39201

James L. Sledge, Jr. State Forester



March 2004

Mississippi's Voluntary Silvicultural Best Management Practices Implementation Monitoring Program

2003 BMP Implementation Survey for Mississippi

Survey Period: November 2002 – July 2003



Prepared by Michael Sampson, Forest Management Division Mississippi Forestry Commission

March 2004

James L. Sledge, Jr. State Forester




TABLE OF CONTENTS

| Acknowledgments | iv |
|--|----|
| Executive Summary | v |
| Introduction | 1 |
| BMPs in Mississippi | 2 |
| BMP Implementation Survey Procedure | 3 |
| BMP Implementation Survey Results | 5 |
| Conclusions | 10 |
| Appendix— | |
| BMP Monitoring State Totals | 13 |
| BMP Monitoring Survey Sites by County | 16 |
| Applicable BMPs Implemented by Category | 17 |
| BMP Categories with Significant Risks to Water Quality | 17 |
| References | 18 |

ACKNOWLEDGMENTS

The 2003 BMP Implementation Survey was made possible through the hard work and dedicated service of the following Mississippi Forestry Commission employees, who make up the agency's Water Quality Team.

Jim Barnes
Randy Bowles
James "Buck" Buchanan
Kenneth E. Cline
Buddy Cuevas
Dennis Dauterive
Bruce Frasier

Brendix Glasgow
Brant Godbold
Nelson Hearn
Greg Jackson
George McCrory
Jim Phillips
John Polk

Steve Prescott
Robert Scoggin
Stuart Sellers
Alan VanValkenburg
Gregory D. Walker
Jeff Ware
Mark Williams

An extended thanks and appreciation goes to the Mississippi Automated Resource Information System, Mississippi State University Extension Service, Mississippi Forestry Association, and the Southern Group of State Foresters.



The Mississippi Forestry Commission provides equal employment opportunity and services to all individuals regardless of disability, race, age, religion, color, gender, creed, national origin, or political affiliation.

EXECUTIVE SUMMARY

In November 2002, the Mississippi Forestry Commission began a survey of best management practices (BMPs) voluntarily implemented on forestland in Mississippi. The survey ended in July 2003. This report presents the results of the survey.

The guidelines set forth in "Silviculture Best Management Practices Implementation Monitoring: A Framework for State Forestry Agencies" were used to develop the 2003 BMP Implementation Survey for Mississippi.

A total of 258 sites having recent silvicultural activity were randomly selected to evaluate the voluntary implementation of best management practices. The sites were also evaluated for the presence of a significant risk to water quality. The Mississippi Forestry Commission's Water Quality Team conducted the survey.

The following criteria were applied in selecting sites to be included in the survey:

- 1) Forest harvesting activity must have occurred within 24 months.
- 2) Sites must be at least 10 acres in size.
- 3) Sites were selected without regard to ownership.

The 2003 BMP Implementation Survey results for Mississippi revealed that 89 percent of best management practices applicable to the survey sites were implemented in accordance with the guidelines published in the handbook *Mississippi's BMPs—Best Management Practices for Forestry in Mississippi'*². Figure 1 shows the BMP categories evaluated during the survey and the implementation results for each category.

Significant risk to water quality occurred on 11 percent of the sites evaluated. The highest percentage (68%) of significant risks was found in the Permanent Roads and Skid Trails/Temporary Roads categories.

Figure 1. BMP categories and implementation results.

INTRODUCTION

Mississippi has nearly 20 million acres of forestland, covering two-thirds of the state's total land area. Forests make an important contribution to Mississippians' quality of life by providing jobs, forest products, livestock forage areas, wildlife habitat, scenic areas, recreational experiences, and many other social and economic benefits. It is estimated that some type of forest activity occurs on nearly 800,000 forested acres each year in Mississippi. Mississippi's forestland also plays a vital role in protecting the state's water resources and maintaining water quality.

The Clean Water Act of 1987 required that proper steps be taken to prevent water pollution. Mississippi's Silvicultural Best Management Practices (BMPs) were established as a result of the Clean Water Act of 1987. Best management practices are non-regulated, voluntary guidelines for silvicultural activities that, when properly applied, will protect water quality from nonpoint source pollutants while maintaining site productivity. Nonpoint source pollution is defined in Section 319 of the Clean Water Act of 1987 as "pollution caused by diffuse sources that are not regulated as point sources and normally associated with agricultural, *silvicultural* [emphasis added] and urban runoff, runoff from construction activities, etc. Such pollution results in human-made or human-induced alteration of the chemical, physical, biological, and radiological integrity of the water."

The Best Management Practices Implementation Monitoring Program was developed to provide a way to measure the voluntary use of BMPs in Mississippi. The Mississippi Forestry Commission intends to conduct BMP Implementation surveys on a three-year cycle.



BEST MANAGEMENT PRACTICES FOR FORESTRY IN MISSISSIPPI

BMPS IN MISSISSIPPI

Mississippi has a voluntary (non-regulatory) best management practices program for forestry. The program began in 1988 when the Department of Environmental Quality requested that the Mississippi Forestry Commission coordinate the development of voluntary best management practices for forestry in Mississippi. The Mississippi Forestry Commission worked with the Mississippi Forestry Association to put together a group of individuals representing a cross section of the forestry community to develop the guidelines. This group included landowners, loggers, forest industry, professional foresters, and the Department of Environmental Quality. Suggestions and comments from other states were also considered in the development of Mississippi's silvicultural BMPs.

The BMP guidelines were approved by the Mississippi Department of Environmental Quality and the Environmental Protection Agency and, in 1989, published in the handbook *Mississippi's BMPs—Best Management Practices for Forestry in Mississippi*². The handbook was revised in 1995 and once again in 2000.

The Mississippi Forestry Commission (MFC) does not have a regulatory role in water quality, but serves to educate interested parties in the proper use of BMPs. The MFC, in conjunction with Mississippi State University, provides training to its field personnel. Mississippi State University Extension Service conducts a logger training program that addresses BMP implementation (see Table 1 below). In addition, the MFC works with the Mississippi Department of Environmental Quality when addressing water quality problems associated with forestry activities. The Mississippi Forestry Commission works with a number of forest industries by providing training courses for industry personnel and, at their request, conducting reviews of their BMP-related operations.

| Table 1. Logger Training Program. | | | | | |
|-----------------------------------|----------------------|-----------------|------------------------|-------------------------------------|--|
| Course Title | # of Classes Held | Total Attendees | Average # per Class | Wood Supplying Firms Represented | |
| Introduction | 143 | 4,969 | 35 | 2,929 | |
| BMPs | 128 | 4,941 | 39 | 2,926 | |
| Safety | 122 | 4,712 | 39 | 2,789 | |
| Business | 66 | 3,067 | 46 | 2,052 | |
| Total | 459 | 17,689 | 39 | 10,696 | |

Source: Mississippi State University Extension Service. Attendance from 5/11/1996 through 1/1/2003.

BMP IMPLEMENTATION SURVEY PROCEDURE

The 2003 BMP Implementation Survey was developed based on the recommendations found in the document "Silviculture BMP Implementation Monitoring: A Framework for State Forestry Agencies" ¹. In order to promote consistent BMP monitoring throughout the southeastern region, the Southern Group of State Foresters adopted this document for use in developing or updating BMP monitoring programs.

Sampling Intensity

The sampling procedure for the 2003 BMP Implementation Survey was designed as recommended in "Sampling and Estimating Compliance with BMPs" ³. The number of sites needed to maximize the validity and credibility of the survey was calculated to be 258, which is +/-5% within the 95% confidence interval. The Mississippi Forestry Commission's 1997 Resource Assessment was used to determine the amount of forest harvesting activity in the state. This information was used to determine the number and distribution of the sites to be included in the survey.

Eligible Survey Sites

Two hundred fifty-eight geographical points of reference were distributed across the state in a manner representative of the distribution of forested areas having the potential need for BMPs. The Mississippi Forestry Commission used aerial reconnaissance to locate the specific points of reference by finding the respective latitude and longitude coordinates. The tract of land closest to each point of reference that met all site selection criteria was identified as an eligible survey site.

Site selection criteria used for the 2003 survey were: (1) sites had to have had some type of forest harvesting activity, either regeneration harvest or thinning, within a period of two years prior to the survey, (2) sites must be at least 10 acres in size, and (3) sites were selected without regard to ownership. The ownership of a site was determined after the site had been selected. This allowed for an unbiased selection and distribution of survey sites in regard to ownership.

Survey Site Evaluation

Once a site was selected, a field visit was made by a member of the MFC's Water Quality Team. When possible, the landowner was contacted and the BMP survey was explained.

When conducting field visits, the Water Quality Team assessed 73 concerns relating to each survey site, including 55 specific best management practices (see BMP Monitoring Inspection Form on pages 13-15). Best management practices were divided into the following categories:

Streamside Management Zones (SMZs)
Stream Crossings
Permanent Roads
Skid Trails/Temporary (Secondary) roads
Site Preparation
Landings
Wetlands

Fireline Construction

If a particular practice within a category did not apply to the survey site, it was recorded as Not Applicable (N/A). All other practices were considered applicable to the site and were evaluated on whether or not they were implemented as specified in Mississippi's BMP handbook ². This method of evaluation allowed each BMP category and, ultimately, the overall BMP implementation program, to be evaluated and the results expressed as a percent of applicable BMPs implemented.

The presence of a significant risk to water quality was noted for each best management practice evaluated. The Water Quality Team used the following standard to determine the presence of a significant risk to water quality: Significant risk to water quality exists if, during a normal rainfall, sediment is likely to be delivered to a permanent water body. The presence of a significant risk did not mean that water quality was impaired on the site.

All information recorded for each BMP was based on observations made at the time of the inspection. The evaluation process did not include any assumptions concerning future activities on the site.



BEST MANAGEMENT PRACTICES FOR FORESTRY IN MISSISSIPPI

2003 BMP IMPLEMENTATION SURVEY RESULTS

The 2003 BMP Implementation Survey revealed that 89 percent of best management practices applicable to the survey sites were implemented.

A total of 258 sites having recent silvicultural activity were randomly selected to evaluate the voluntary implementation of best management practices. A compilation of all survey data collected is found on the BMP Monitoring Inspection Form—State Totals (see pages 13–15).

General Tract Information

Silvicultural activity: A regeneration harvest had occurred on 232 sites (90%) of the 258 sites surveyed. The remaining 10 percent of the sites involved thinning operations. Of the sites that had received a regeneration harvest, 121 had been artificially regenerated.

Tract size: The sites ranged in size from 10 acres to over 161 acres. Figure 2 shows the distribution of survey sites by tract size.

Ownership: The survey sites were distributed and selected without regard to ownership in order to ensure an unbiased sample. Ownership was determined after a site was located. Figure 3 shows the distribution of survey sites in regard to ownership. The 258 survey sites were in the following four forest ownership groups:

Private Nonindustrial—
(153 survey sites, 59.3% of survey)

State/Public— (20 survey sites, 7.8% of survey)

Federal— (1 survey site, 0.4% of survey)

Forest Industry— (84 survey sites, 32.6% of survey).




Figure 2. Distribution of survey sites by tract size.

Survey Sites

(Distribution by Ownership)




Figure 3. Distribution of survey sites by ownership.

Counties: The BMP survey sites were randomly distributed across the state based on the potential need for BMPs as determined by the change in forest cover shown in the Mississippi Forestry Commission's 1997 Resource Assessment. Survey sites were located in 74 of the 82 Mississippi counties. See Table 2 BMP Survey Sites by County, page 16.

River basins: For each site inspected for BMP monitoring, the river basin containing the site was identified. Survey sites were located in 10 of Mississippi's 11 river basins as delineated in the Mississippi Department of Environmental Quality's Basin Management Program. No survey sites where located in the Upper Mississippi River basin. The river basins of Mississippi are shown below in Figure 4.




Figure 4. River Basins of Mississippi.

Survey Sites with Applicable BMPs by Categories

The number of survey sites on which BMP categories were applicable is shown in Figure 5. (This information is also found in Table 3, page 17.)

The BMP categories Permanent Roads, Skid Trails/Temporary Roads, and Landings were applicable on more survey sites than the other categories. The Permanent Roads category was applicable on 217 (84.1%) of the 258 survey sites. The Skid Trails/Temporary Roads category was applicable on 248 (96.1%) and Landings on 254 (98.4%) of the survey sites.

The Streamside Management Zones category was applicable on 170 (65.9%) of the 258 sites surveyed, while Stream Crossings applied on 130 (50.4%) sites.

The three remaining categories (Site Preparation, Wetlands, and Fireline Construction) applied less frequently than




Figure 5. Number of survey sites for each BMP category.

any of the preceding categories. Site Preparation applied on 121 (46.9%) of the 258 survey sites, Fireline Construction applied on 64 (24.8%), and Wetlands on 6 (2.3%) sites.

BMP Implementation

Applicable BMPs were evaluated on whether or not they were implemented as specified in Mississippi's BMP handbook ². Results showed that eighty-nine percent of best management practices were implemented on survey sites where they were applicable (see Table 3, page 17).

Implementation results were also evaluated by BMP category. Figure 6 shows the implementation results for each BMP category. The number and percent of all applicable BMPs implemented for each category is presented in Table 3, page 17.

The lowest percentage of BMPs implemented was found in the Skid Trails/Temporary Roads category with 80.9% of the 1,195 applicable practices implemented as specified. Of the 2,299 practices in the Permanent Roads category, 89.4% were implemented as specified, and 93.1% of the 1,212 practices in the Landings category were implemented as specified.

The Streamside Management Zones category had 89.6% of the 1,580 applicable practices implemented as specified, and the Stream Crossings category had 88.8% of the 581 applicable practices implemented as specified.

Applicable BMP practices in the Site Preparation category had the highest percentage implemented as specified with 95.3% of the 880 applicable practices implemented according to specifications. Of

the 18 applicable practices in the Wetlands category, 94.4% were implemented, and 81.3% of the 386 practices in the Fireline Construction category were implemented as specified.

2003 BMP Implementation Results



Figure 6. BMP categories and implementation results (percent).

Significant Risk to Water Quality

Sites were evaluated for a significant risk to water quality each time a best management practice was determined to be applicable to the survey site. Of the 8,151 applicable BMPs evaluated, a significant risk to water quality was observed 76 times. These occurred on 29 of the 258 sites surveyed. Thirty-two of the 76 occurred on three sites. A complete listing of significant risks by individual best management practice is found on the BMP Monitoring Inspection Form—State Totals (see pages 13-15). A summary of significant risks by BMP category is given in Table 4, page 17.

No significant risks to water quality were found associated with practices in the Site Preparation or Wetlands categories.

Twelve significant risks to water quality were observed in relation to BMPs associated with streamside management zones. These 12 significant risks were found on five of the 170 survey sites where SMZs were applicable.

In the Stream Crossings category, six significant risks to water quality were found on four of the 130 sites where stream crossings were applicable.

There were 29 significant risks to water quality observed in the Permanent Roads category. These occurred on 16 of the 217 sites with permanent roads. The Permanent Road category had a higher

percentage of significant risks to water quality than any other BMP category. The majority of these were associated with the practice *roads reshaped and/or stabilized*. This practice was not implemented on 60 applicable survey sites.

Twenty-three significant risks were observed on 14 of the 248 sites where BMPs were associated with skid trails or temporary roads. Of the 23 significant risks, 11 were associated with roads or skid trails not stabilized during or after completion of harvest.

Four significant risks to water quality applied to BMPs associated with landings. These four were associated with the best management practice *restoring/stabilizing loading ramps*.

There are 386 applicable practices for Fireline Construction on 64 sites. Two significant risks to water quality were noted for the category.

CONCLUSIONS

Our forests play an essential role in the protection of water quality. They absorb rainfall, filter pollutants, and recharge underground water supplies. Forests produce much of the clean water we need for recreation and support of fish and wildlife habitats as well as the drinking water supply for millions of Americans.

Despite the tremendous contribution our forests and forestry make to water quality, forestry activities have the potential to adversely impact water quality locally. Voluntary best management practices are utilized in Mississippi to address this potential and help ensure water quality is protected. Studies have shown that BMP efforts work when applied on a landowner's property. The Mississippi Forestry Commission's 2003 BMP Implementation Survey for Mississippi was conducted to assess the implementation of the voluntary BMPs in the state.

It is essential that the forestry community continue its efforts to protect water quality and monitor protection efforts. The Mississippi Forestry Commission, Southern Group of State Foresters, and National Association of State Foresters are committed to the protection of our forests and water and to the routine assessment of protection measures implemented by the forestry community.



BEST MANAGEMENT PRACTICES FOR FORESTRY IN MISSISSIPPI

APPENDIX

Mississippi Forestry Commission BMP Monitoring Inspection Form State Totals

| 1. General Tract Information Siliviculture Activity Regeneratio Estimated Tract Size Acre 10 | 40 41 - 80 | 26 85 81 - 120 | <u>54</u> 121 - 10 | 50 | 20 |
|--|--|--|-----------------------------|-------------|-----------|
| Ownership Group PNII Mississippi's River Basins Big Black River Basin North Independent Streams Basin South Independent Streams Basin Pascagoula River Basin Tennessee River Basin Lower Mississippi River Basin Tombigbee River Basin Upper Mississippi River Basin Pearl River Basin | 18 sin 8 | 20 FEDERAL | 1 INDUS | TRY | 84 |
| Yazoo River Basin | 28 | | | | |
| 2. Site Characteristics Estimate Slopes Present 0% - 5% Predominant Soil Texture Clay Sandy Loa Erodibility Hazards Low | 99 6% - 20% 27 Clay Loam m 98 Sand 92 Medium | 118 21% - 40% 105 Loam 0 Silty Soils 117 High | 37 Over 4 16 12 49 | 40% _ | 4 |
| Type of Stream Present Perennial Stream | 43 Intermittent Stream | 75 Ephemeral Stre | am 82 N | I/A | 58 |
| Estmate Distance to Nearest Permand 300 Ft. or Less 32 Evidence of Spills or Fuels On Site Trash, Oil Cans, Hoses Or Other Con Has Tract Been Regenerated artificia | 301 - 800 Ft. 36 801 Yes 4 ntainers Left On Site Yes | - 1600 Ft. 41 No 254 15 No 2 137 | 1601 Ft. or More | | 149 |
| 3. Streamside Management Zones | | N/A | Yes | No | Sig. Risk |
| SMZ width established according to | BMP specs | 95 | 141 | 22 | 2 |
| Harvesting/thinning within SMZ acc | | 103 | 134 | 21 | 1 |
| SMZ integrity honored (no chem, fer | | MZ) 99 95 | 146 | 13 25 | 2 |
| Stream Course Clear of Logging Deb SMZ Free of Roads and Landings | 1115 | 93 - | 156 | | 1 |
| Stream Free of Sediment Due to Silva | icultural Activity | 92 - | 146 | 20 | 1 |
| Rutting Through Streams or Drains | | 97 | 147 | 14 | 0 |
| Prescribed Burning Avoided | | 139 | 113 | 6 | 1 |
| Blocking the Natural Flow of Water | Avoided | 91 | 148 | 19 | 2 |
| Stream Banks Integrity Honored | | 96 | 147 | 15 | 1 |
| | Section Totals % Compliance | 90 % | 1,416 | 164 | 12 |
| 4. Stream Crossings | | | | | |
| Ditches That Dump Into Streams Av | oided | 133 | 113 | 12 | 0 |
| Stream Crossings Properly Installed | | 145 | 93 | 20 | 3 |
| Number of Stream Crossings Minim | zed | 141 | 113 | 4 | 0 |
| Stream or Drain Crossings Installed Stream Crossings Stabilized During | At Kight Angle Only | 143 | 90 | 8 21 | 3 |
| Stream Crossings Stabilized During | | | | | |
| | Section Totals % Compliance | 89% | 516 | 65 | 6 |

Mississippi Forestry Commission BMP Monitoring Inspection Form

| Diff. Monitoring suspenses | N/A | Yes | No | Sig. Risk |
|--|---|-------|-----|-----------|
| . Permanent Roads | N/A 45 | 209 | 4 | 1 |
| Roads Respect Sensitive Area | 43 | 190 | 26 | 4 |
| Rutting Depth Does Not Exceed Six Inches For More Than Fifty Feet | 42 — | 208 | 8 | |
| Roads Located Where Side Drainage Can Be Achieved | 42 | 206 | 10 | 1 |
| Roads Wide Enough to Achieve Surface Drying | 41 — | 157 | 60 | 11 |
| Roads Reshaped and/or Stabilized | 42 | 185 | 31 | 2 |
| Roads Meet Grade Specification | 63 | 162 | 33 | 2 |
| Roads Are Well Drained With Appropriate Structures (bridges, culverts, etc.) | 67 | 172 | 19 | 2 |
| Side Ditches Do Not Dump Into Streams | 49 — | 184 | 25 | 1 |
| Flat No Grade Roads Avoided | 59 | 187 | 12 | 1 |
| Streambeds, Rocky Places, and Steep Slopes Avoided | 47 — | 195 | 16 | 4 |
| Potential Problem Soils Avoided | | | | |
| Section Totals | | 2,055 | 244 | 29 |
| % Compliance | 89% | | | |
| 6. Skid Trails/Temporary (secondary) Roads | *************************************** | | | |
| Sensitive Areas Respected | 21 | 219 | 18 | 1 |
| Majority of Skid Trail Grades (Steepness) Below 15% | 12 | 219 | 27 | 2 |
| Rutting Does Not Exceed Six Inches For More Than Fifty Feet | 12 | 209 | 37 | 4 |
| Water Bars, Turnouts, and Other Water Control Structures Present | 35 | 148 | 75 | 5 |
| Roads and Skid Trails Are Stabilized | 15 | 172 | 71 | 11 |
| | | 967 | 228 | 23 |
| Section Total % Compliance | 81%— | 907 | | |
| | | | | |
| 7. Site Preparation Sensitive Areas Respected | 151 | 102 | 5 | 0 |
| Contour Followed | 160 | 96 | 2 | 0 |
| SMZ Integrity Honored(No chem, fert, burning, log decks, etc. within SMZ) | 170 | 82 | 6 | 0 |
| Soil Disturbance Kept To A Minimum | 147 | 104 | 7 | 0 |
| Excessive Soil Compaction Avoided | 146 | 110 | 2 | 0 |
| Does It Appear That Chemicals Were Used According To Label Spec | 186 | 70 | 2 | 0 |
| Disturbance On Slopes Minimized | 147 | 103 | 8 | 0 |
| Water Diverted From Site Prep Area To Vegetated Surface | 157 | 96 | 5 | 0 |
| Extremely Hot Burns Avoided | 178 | 76 | 4 | 0 |
| 0 M m 1 | | 020 | 41 | 0 |
| Section Total | 95% | 839 | 41 | |
| % Compliance | 9370 | | | |
| 8. Landings | | | | |
| Location Outside of SMZ | 48 | 208 | 2 | 0 |
| Well-Drained Location | 4 | 246 | 8 | 0 |
| Number and Size Minimized | 4 | 252 | 2 | 0 |
| Sensitive Areas Respected | 16 | 240 | 2 | 0 |
| Restored Stabilized | 6 | 182 | 70 | 4 |
| Section Total | | 1,128 | 84 | 4 |
| % Compliance | 93% | | | |
| % Compnance | 9370 | | | |

Mississippi Forestry Commission BMP Monitoring Inspection Form

| 9. Wetlands | N/A | Yes | No | Sig. Risk |
|--|--|-----|-----|---|
| Hydrology of Site Unaltered | 252 | 5 | 1 | 0 |
| Roads, Drainage Structures Applied Properly | 252 | 6 | 0 | 0 |
| Mandatory BMP's Followed | 252 | 6 | 0 | 0 |
| Section 7 | otals | 17 | 1 | 0 |
| % Comp | liance 94% | _ | | |
| 10. Fireline Construction | | | | *************************************** |
| Firebreak Erosion Controlled | 196 | 48 | 14 | 0 |
| Majority of Fireline Constructed Around Slopes or Grade of Less Th | an 10% 196 | 54 | 8 | 1 |
| Water Bars, Turnouts and Other Water Control Structures Properly | nstalled 199 | 34 | 25 | 0 |
| Diversion Ditches Not Constructed at the Head of a Drain | 198 | 53 | 7 | 0 |
| Firelines Not Constructed Down the Slope of Natural Gully | 200 | 54 | 4 | 0 |
| SMZs Left Between the Fireline and Stream | 217 | 35 | 6 | 0 |
| Avoid Constructing Firelines into an SMZ | 214 | 36 | 8 | 1 |
| Section To | itals | 314 | 72 | 2 |
| % Compli | | | | · · · · · · · · · · · · · · · · · · · |
| Follow Up Questions | | | | |
| Was Activity Supervised By Professional Forester? | 115 | 133 | 10 | |
| Was Landowner Familiar With BMP Handbook? | 140 | 101 | 17 | |
| Was Logger Familiar With BMPs? | 140 | 112 | 6 | |
| Were BMPs Included in Contract? | 188 | 56 | 14 | |
| Has Logger Completed Logger Educational Training Courses? | 181 | 66 | 11 | |
| Are Recommendations Planned for Landowner, if Needed? | 140 | 70 | 48 | |
| Section 7 | otals . | 538 | 106 | |
| % Comp | | | | |
| State To % Comp | A CONTRACTOR OF THE CONTRACTOR | | | |

Table 2. BMP Survey Sites by County.

| County | Change of Forest Cover 1 (percent) | Survey Sites | County | Change of Forest Cover ¹ (percent) | Survey Sites |
|-------------|------------------------------------|-----------------|--------------|--|-----------------|
| Adams | 0.13 | 0 | Leflore | 0.46 | 1 |
| Alcorn | 0.79 | 2 | Linclon | 1.76 | 5 |
| Amite | 1.27 | 3 | Lowndes | 1.08 | 3 |
| Attala | 1.27 | 3 | Madison | 1.28 | 3 |
| Benton | 0.83 | 2 | Marion | 1.26 | 3 |
| Bolivar | 1.23 | 3 | Marshall | 2.08 | 6 |
| Calhourn | 1.33 | 4 | Monroe | 0.85 | 2 |
| Carroll | 0.76 | 2 | Montgomery | 1.03 | 3 |
| Chickasaw | 0.42 | 1 | Neshoba | 2.16 | 6 |
| Choctaw | 1.93 | 5 | Newton | 2.76 | 8 |
| Claiborne | 0.33 | 1 | Noxubee | 1.34 | 4 |
| Clarke | 2.43 | 7 | Oktibbeha | 1.19 | 3 |
| Clay | 0.86 | 2 | Panola | 0.44 | 1 |
| Coahoma | 0.17 | 0 | Pearl River | 3.15 | 9 |
| Copiah | 2.55 | 7 | Perry | 1.25 | 3 |
| Covington | 0.77 | 2 | Pike | 1.31 | 3 |
| De Soto | 0.16 | 0 | Pontotoc | 0.34 | 1 |
| Forrest | 1.08 | 3 | Prentiss | 0.97 | 2 |
| Franklin | 1.36 | 4 | Quitman | 0.14 | 0 |
| George | 0.83 | 2 | Rankin | 2.77 | 8 |
| Greene | 1.5 | 4 | Scott | 2.02 | 6 |
| Grenada | 0.98 | 2 | Sharkey | 0.31 | 0 |
| Hancock | 1.44 | 4 | Simpson | 1.81 | 5 |
| Harrison | 1.19 | 3 | Smith | 1.67 | 5 |
| Hinds | 1.65 | 4 | Stone | 1.33 | 3 |
| Holmes | 0.81 | 2 | Sunflower | 0.83 | 2 |
| Humphreys | 0.51 | 1 | Tallahatchie | 0.49 | 1 |
| Issaquena | 0.57 | 1 | Tate | 0.15 | 0 |
| Itawamba | 0.83 | 2 | Tippah | 0.6 | 1 |
| Jackson | 1.16 | 3 | Tishomingo | 1.51 | 4 |
| Jasper | 1.5 | 4 | Tunica | 0.2 | 0 |
| Jefferson | 0.58 | 1 | Union | 0.39 | 1 |
| Jeff. Davis | 0.86 | 2 | Walthall | 0.66 | 1 |
| Jones | 1.28 | 3 | Warren | 0.76 | 2 |
| Kemper | 3.51 | 10 | Washington | 1.25 | 3 |
| Lafeyette | 2.55 | 7 | Wayne | 2.06 | 6 |
| Lamar | 1.25 | 3 | Webster | 1.5 | 4 |
| Lauderdale | 3.98 | 11 | Wilkinson | 0.57 | 1 |
| Lawrence | 0.76 | 2 | Winston | 2.22 | 6 |
| Leake | 2.05 | 6 | Yalobusha | 1.28 | 3 |
| Lee | 0.18 | 0 | Yazoo | 0.97 | 2 |
| | | | | | |

¹ The 1997 Resource Assessment was used to determine percent change of forest cover. Source: Mississippi Automated Resource Information System (MARIS).

Table 3. Applicable BMPs Implemented by Category.

| BMP Category | Number of | Total Applicable | BMPs Implemented * | |
|-----------------------------|--------------|---------------------|--------------------|---------|
| | Survey Sites | Practices | Number | Percent |
| Streamside Management Zones | 170 | 1,580 | 1,416 | 89.6 |
| Stream Crossings | 130 | 581 | 516 | 88.8 |
| Permanent Roads | 217 | 2,299 | 2,055 | 89.4 |
| Skid Trails/Temporary Roads | 248 | 1,195 | 967 | 80.9 |
| Site Preparation | 121 | 880 | 839 | 95.3 |
| Landings | 254 | 1,212 | 1,128 | 93.1 |
| Wetlands | 6 | 18 | 17 | 94.4 |
| Fireline Construction | 64 | 386 | 314 | 81.3 |
| State Totals | _ | 8,151 | 7,252 | 89.0 |

 $^{^{\}star}$ BMPs implemented as specified in Mississippi's BMP handbook $^{2}.$

| Table 4. BMP Categories with Significant Risk | s to water Quality., |
|---|----------------------|
|---|----------------------|

| BMP Category | Number | Percent |
|-----------------------------|--------|---------|
| Streamside Management Zones | 12 | 15.8 |
| Stream Crossings | 6 | 7.9 |
| Permanent Roads | 29 | 38.1 |
| Skid Trails/Temporary Roads | 23 | 30.3 |
| Site Preparation | 0 | 0.0 |
| Landings | 4 | 5.3 |
| Wetlands | 0 | 0.0 |
| Fireline Construction | 2 | 2.6 |
| State Totals | 76 | 100.0 |

REFERENCES

- ¹ "Silvicuture Best Management Practices Implementation Monitoring: A Framework for State Forestry Agencies," BMP Monitoring Task Force, Southern Group of State Foresters, June 2002.
- ² Mississippi's BMPs—Best Management Practices for Forestry in Mississippi, Third Edition, Mississippi Forestry Commission, March 2000.
- ³ McNew, Ronald W., "Sampling and Estimating Compliance with BMPs," Implementation Monitoring of Forestry Best Management Practices Workshop, Southern Group of State Foresters and USDA Forest Service, Atlanta, Georgia, January 23-25, 1990. Edited by G. Dissmeyer.



BEST MANAGEMENT PRACTICES FOR FORESTRY IN MISSISSIPPI

